



RCS-430LBTPC-PCAP

43" All In One Windows Display

Right Message At Right Time



Rcstars All-In-one PC adopts Intel core processors, and streams an entire screen system into an elegant, powerful device with the ability to create, stream and share HD Content, you can work and play with more confidence, All in one is well suited for both touch and non touch applications. Featuring a unique quick disconnect PC design, multiple I/O Ports, makes the most of your digital world. All in one touch screen computers could be used in a wide range markets, such as gaming machines, hospitality systems, industrial automation, interactive kiosks, point of sale system and retail displays.

Key Features:

CPU: Intel® Core® Processor, I3 5010U
(Dual core four thread, 3M L3 Cache, 2.1GHz)
Chipset: Haswell-U
Graphic Card: Intel HD5500
Memory: 4GB RAM, 120G SSD
Audio: Realtek ALC662
Ethernet LAN: 1*RTL8111F LAN

Application:

Security
Transportation
Atm Automation
Medical Equipment
Gaming Machine
Networking Pos
General Application

43" All In One Windows Display



Specifications

| | | | | | |
|-----------------------|----------------------|--|-------------------------|---|---|
| PANEL | Panel Model | 43inch TFT LED | RESOLUTION REFRESH RATE | Output Mode | 1920 x 1200 60Hz |
| | Max Resolution | 1920x1080 | | | 1920 x 1080 60Hz |
| | Aspect Ratio | 16:09 | | | 1600 x 1200 60Hz |
| | Pixel Pitch | 0.4903x0.4903 | | | 1440 x 900 60Hz |
| | Viewing Angle | 89/89/89/89 | | | 1366 x 768 60Hz |
| | Contrast Ratio | 1200:1 | | | 1360 x 768 60Hz |
| | Brightness | 500cd/m² | | | 1280 x 1024 60Hz |
| | Response Time | 26ms | | | 1280 x 800 60Hz |
| | Display Area (mm) | 941.184x529.416mm | | | 1280 x 768 60Hz |
| | Panel Size(mm) | 973x565.8x29mm | | | 1024 x 768 60Hz |
| | Screen Weight | 11Kg | | | 800 x 600 56, 60, 72, 75Hz |
| | Lamp Type | WLED | | | 640 x 480 60, 67, 72, 75Hz |
| CELERON SPECIFICATION | CPU | Intel® Core® Processor, i3 5010U (Dual core four thread, 3M L3 Cache, 2.1GHz) | TOUCH | P-CAP Touch / infrared Touch (optional) | |
| | Chipset | Haswell-U | POWER | Mains Power Consumption | AC 100-240V, 50-60 Hz 65 W |
| | Bios | Intel HD5500 | | | |
| | Memory | 4GB RAM, 120G SSD | SOUND | Built-in Speakers | 2 x 10W |
| | Audio | Realtek ALC662 | DIMENSION & WEIGHT | Machine Size | 1800x65x639mm |
| | Ethernet LAN | 1*RTL8111F LAN | | Machine Weight | 641x50x435mm(stand base) |
| CONNECTOR | Rear Panel I/O | X1 HDMI port | | Carton Size | 53KG / 12.5KG(stand base) |
| | | X1 VGA port | | Carton Weight | 1930x180x770mm |
| | | X1 RJ-45 port | | Carton Weight | 73KG |
| | | X2 USB 2.0 ports and 2 * USB 3.0 ports | | Wooden Case Size | 1980x950x850mm (5PCS) |
| | | X2 Audio I/O ports (Mic and Line-out) | | Wooden Case Weight | 438KG |
| CONNECTIVITY | LAN | RJ45 Port, 10/100M Ethernet | OTHER | Regulatory Approvals | CE, FCC, ROHS |
| | WiFi | Built-in WiFi 802.11B/G/N | | Warranty | 1 year warranty |
| | 3G (Optional) | WCDMA | ACCESSORIES | Included | AC Power Cord, CD, Tools and Screws, User manual, Keys |
| MULTIMEDIA | USB Playback Audio | AAC, AIF, AIFF, ASF, LPCM, M3U, M4A, MP3, MP4, WAV, WMA | | | |
| | USB Playback Picture | BMP, GIF, JPEG, JPG | | | |
| | USB Playback Video | M2TS, M4V, MK3D, MKV, MP4, MPEG, MPG, MTS, TS, TTS, VOB, WMV | | | |