



Nord Technology

Reseller af Rostars hardware in Denmark

NORD TECHNOLOGY CONTACT INFORMATION

World Trade Center

Borupvang 3,

2750 Ballerup,

Denmark

Tel.: +45 70 27 04 15

Email: sales@nord-t.eu

RCS-430LYAZ





Indoor High Brightness 43" Roll Display

Right Message At Right Time

RCS-430LYAZ



Digital Signage is the remote-controlled distribution and playback of digital content (TV programs, advertising, menus, and every sort of information) on networks of displays. These displays can range from digital billboards to much smaller screens, either at a single location or across multiple sites. It's all about targeting the audience with relevant information. Digital signage enables users to display their messages more dynamically and targeted.

RCSTARS has demonstrated a Digital Signage application on android platform. The application provides the features of updating the content from remote web browser, playback of video content, image, HTML web pages and scrolling text messages.

Key Features:

- · Android 7.1 operating system
- Rockchip RK3288 Quad-core CPU
- 2/4GB DDR3 + 8/16/32 GB Flash
- 802.11a/b/g/n/ac internal Wifi
- 4G/WIFI/WLAN Network connection
- Remote Management Software
- · Portrait & Landscape display mode
- 1080P Display output
- The battery life is 10 hours
- · Low glare glass


Application Areas

- POS
- Hotel
- · Self-service Terminal
- Public Information Display
- Hospitality
- In-vehicles And Transportation




Indoor High Brightness 43" Roll Display

RCS-430LYAZ







Specifications

DISPLAY	Panel Model Max Resolution Aspect Ratio Pixel Pitch Viewing Angle Contrast Ratio Brightness Response Time	43 inch TFT LED 1920×1080 16:09 0.49005×0.49005 89/89/89/89 1200:1 1500 cd/m² 8 ms
	Display Area (mm)	941.184×529.416 mm
	Panel Size(mm)	973×565.8×29 mm
	Screen Weight	11 kg
	Lamp Type	WLED
INTERNAL MEDIA PLAYER	CPU	Quad-core ARM Cortex-A17,1.8GHz
	GPU	ARM Mali-T764
	RAM	2/4GB DDR3
	ROM	8/16/32 GB Flash
	OS	Android 7.1
CONNECTOR	USB	×2
	LAN	×1
CONNECTIVITY	WiFi	Built-in WiFi 802.11a/b/g/n/ac
	4G (Optional)	LTE
FILE SUPPORT	Video	H.264, MKV, WMV9, MPEG 1/2/4,
		HD Divx, Xvid, RM/RMVB
	Image	BMP/PNG/GIF/JPEG
	Audio	MP3, WMA, WAV, EAAC+, MP2 dec,
		Vorbis (Ogg), AC3, FLAC, APE, BSAC
	Scrolling Text	txt
DISPLAY MODE		Portrait
TOUCHPCAP		Capacitive Touch options

PERATURE CONTROLLER		TemCooling fan can be set to start running when the whole temperature reached 60 °C
COOLING SYSTEM	Blowing machine Cooling fan Noise dB(A)	Air cooling system: 45 blowing machines and ocoling fans, stable and reliable performance <55 dB
LEVEL OF PROTECTION		IP 54
ON-SCREEN DISPLAY LANGUAGES		English, French, German, Italian, Polish, Russian, Simplified Chinese, Spanish, Turkish, Arabic, Japanese, Traditional Chinese etc.
POWER	Out put Consumption	DC 29.4 V 88 W
SOUND	Built-in Speakers	2×5 W
DIMENSION & WEIGHT	Machine Size Machine Weight Carton Size Carton Weight	57 kg 94 kg 1105×395×605 mm 1280×560×840 mm
OTHER	Regulatory Approvals Warranty	CE, FCC, ROHS 2 years warranty
ACCESSORIES	Included	Remote Control, Power supply, User manual, Keys, Screws