

Nord Technology

Reseller of Rstars hardware in Denmark

NORD TECHNOLOGY CONTACT INFORMATION

World Trade Center
Borupvang 3,
2750 Ballerup,
Denmark

☎ **Tel.:** +45 70 27 04 15
✉ **Email:** sales@nord-t.eu
🏠 **Website:** www.nordtechnology.dk

RCS-430ODLYAZ





Digital Signage is the remote-controlled distribution and playback of digital content (TV programs, advertising, menus, and every sort of information) on networks of displays. These displays can range from digital billboards to much smaller screens, either at a single location or across multiple sites. It's all about targeting the audience with relevant information. Digital signage enables users to display their messages more dynamically and targeted.


RCSTARS has demonstrated a Digital Signage application on android platform. The application provides the features of updating the content from remote web browser, playback of video content, image, HTML web pages and scrolling text messages.

Key Features:

- Android 7.1 operating system
- Rockchip RK3288 Quad-core CPU
- 2/4GB DDR3 + 8/16/32 GB Flash
- 802.11a/b/g/n/ac internal Wifi
- 4G/WIFI/WLAN Network connection
- Remote Management Software
- Portrait & Landscape display mode
- 1080P Display output
- The battery life is 10 hours
- Low glare glass

Application Areas

- POS
- Hotel
- Self-service Terminal
- Public Information Display
- Hospitality
- In-vehicles And Transportation



Specifications

DISPLAY	Panel Model	43 inch TFT LED
	Max Resolution	1920×1080
	Aspect Ratio	16:09
	Pixel Pitch	0.49005×0.49005
	Viewing Angle	89/89/89/89
	Contrast Ratio	1200:1
	Brightness	2000 cd/m ²
	Response Time	8 ms
	Display Area (mm)	941.184×529.416 mm
	Panel Size(mm)	973×565.8×29 mm
	Screen Weight	11 kg
	Lamp Type	WLED
INTERNAL MEDIA PLAYER	CPU	Quad-core ARM Cortex-A17, 1.8GHz
	GPU	ARM Mali-T764
	RAM	2/4GB DDR3
	ROM	8/16/32 GB Flash
	OS	Android 7.1
CONNECTOR	HDMI input	×1
	USB	×2
	WLAN	×1
CONNECTIVITY	WiFi	Built-in WiFi 802.11a/b/g/n/ac
	4G (Optional)	LTE
FILE SUPPORT	Video	H.264, MKV, WMV9, MPEG 1/2/4, HD Divx, Xvid, RM/RMVB;
	Image	BMP/PNG/GIF/JPEG
	Audio	MP3, WMA, WAV, EAAC+, MP2 dec, Vorbis (Ogg), AC3, FLAC, APE, BSAC
	Scrolling Text	txt
DISPLAY MODE		Portrait
TOUCHPCAP		Capacitive Touch options

PERATURE CONTROLLER		TemCooling fan can be set to start running when the whole temperature reached 60 °C
COOLING SYSTEM	Blowing machine	Air cooling system: 45 blowing machines and 15 cooling fans, stable and reliable performance
	Cooling fan	<55 dB
LEVEL OF PROTECTION		IP 65
ON-SCREEN DISPLAY LANGUAGES		English, French, German, Italian, Polish, Russian, Simplified Chinese, Spanish, Turkish, Arabic, Japanese, Traditional Chinese etc.
POWER	Out put	DC 24 V
	Consumption	110 W
SOUND	Built-in Speakers	2×5 W
DIMENSION & WEIGHT	Machine Size	1104.59×407×613 mm
	Machine Weight	50 kg
	Carton Size	1150×455×700 mm
	Carton Weight	59 kg
	Wooden Case Size	1205×555×850 mm (1PCS)
	Wooden Case Weight	75 kg
OTHER	Regulatory Approvals	CE, FCC, ROHS
	Warranty	1 years warranty
ACCESSORIES	Included	Remote Control, Power supply, User manual, Keys, Screws